



DXP

Sunoco DXP was developed to exceed the needs of engines that push bore size, high compression ratios and extreme rpm levels. Sunoco DXP delivers extra protection against detonation during the best atmospheric conditions for improved performance within a demanding feature race or endurance events. This precision blends allows for greater durability and reduced wear in today's top level race engines.

Sunoco DXP is for off-road and racing use only. It contains additives to enhance stability and minimize oxidative effects. As with any gasoline, DXP should be stored in opaque, tightly sealed containers where temperatures are stable. Handled under such conditions, the shelf life of Sunoco DXP is 3 years or more.

DISCLAIMER:

Legal in California only for racing vehicles in sanctioned racing events.

LEGAL:

For off-road and racing applications only.

TECHNICAL DETAILS

Color	Green
Octane (R+M)/2	116
Research Octane	119
Motor Octane	113
Specific Gravity	0.735
Weight (lbs/gallon)	6.1
Reid Vapor Pressure	5.0
10% Evaporation	178
50% Evaporation	216
90% Evaporation	225
Stoichiometric Air/Fuel Ratio	14.9
Oxygen (Weight%)	0
Ethanol (Volume%)	0
HC Ratio	2.07
Lower Heating Value (Btu/Pound)	18,600
Lower Heating Value (Btu/Gallon)	113,100
Leaded	Yes

APPLICATIONS

Boats and Personal Watercraft	Muscle Cars and Vintage Cars
Dirt Oval	Off-Road
Highly Boosted Engines	Truck and Tractor Pulling
Miscellaneous Nitrous, Superchargers, Turbochargers	Vintage

SANCTIONING BODIES